



Marine Grade Camera Range

SSMPT 10 PTZ Stainless Steel 316 Mini PTZ Dome Camera

Main Features Include:

- 600TVL Sony Super HAD CCD
- Day / Night switching using IR Cut
- Minimum Illumination: 0.06 Lux
- 10x Optical Zoom (3.8mm - 38mm)
- 10x Digital Zoom (total 100x Zoom)
- Pan speed 300 degree per sec
- Tilt speed 300 degree per sec
- 128 Preset Positions
- Tours: 6 Programmable
- Power Source 12V DC 500mA
- Dome: Diameter 96mm
- IP65 Weather Proof Housing
- Housing: Marine Grade Stainless Steel 316

Specification may change without prior notice



DOME DIAMETER ONLY 96MM



THE CAMERAS BUILT IN FANS & HEATERS PROTECT THE CAMERA TO 25°F BELOW ZERO



**IDEAL FOR
HARSH SALT
WATER
ENVIRONMENTS**

A HIGH PERFORMANCE SPEED DOME OFFERING SUPERIOR PICTURE QUALITY IN AN EXTREMELY ROBUST STAINLESS STEEL HOUSING



Marine Grade Camera Range

SSMPT10 PTZ Stainless Steel 316 Mini PTZ Dome Camera



Technical Data

Model	SSMPT10
Image Device	1/4" Interline Transfer CCD PAL
High Resolution	600 TV Lines
S/N Ratio	50 dB [AGC Off]
Zoom	x10 Optical Zoom, x100 Digital Zoom
Focal Length	F1.8, f=3.8 ~ 38mm
Minimum Illumination	0.7 Lux Colour / 0.2 Lux B&W @ 50 IRE
Day & Night	Auto Day Night - ICR
Focus	Auto Manual Semi-Auto
Iris	Auto Manual
Shutter Speed	x128 ~ 1/200000 sec
AGC	Normal High Off
White Balance	Auto Manual - Red, Blue Gain Adjustable
BLC	Low Middle High Off
Flickerless	Selectable
SSNR	NIL
Other Functions	Frame Freeze Function, System Image Flip by Installation Tape
Preset	128 Presets with Labels / Independent Present Characteristic Setup
Pattern	4 Patterns - Approx. 5 Minutes for Each Pattern
Swing	8 Swings
Group	8 Groups - MAX. 20 Entries for each Group
Other Functions	Auto Flip, Auto Parking, Power-up Action & etc
Communication	RS-485, Privacy Zone 4 Zones
Protocol	Pelco-D, Pelco-P Selectable

